

## FORESTRY MULCHERS FOR SKID STEERS

# PMM/SSL

### Brush mulcher with hammer/flail rotor for skid steers.

A universal mulcher suitable for mulching saplings, bushes, crop residues and grass. Thanks to its "floating system", the mulcher's rotor adheres perfectly to the terrain, ensuring a homogeneous material after mulching. The support roller, larger in comparison to other attachments, guarantees the best performance

even on particularly damp terrain. The machine can be equipped with hammers for mulching material up to 8 cm diameter or grass flail to better respond to the various needs of the customer.

 65-100 hp

 Ø 8 cm max



**Steel counter-blades**  
helps mulch material into a smaller final size



**Self leveling protection flaps**

**Attachment plate with self leveling device**  
adapts to all types of terrain



**Self cleaning rear roller with integrated skids**



#### STANDARD EQUIPMENT

|  |   |
|--|---|
| 32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve | Self levelling protection flaps                 |
| Motor enclosed in the frame  | Supporting service leg                          |
| Belt transmission  | Welded counterblades                            |
| Hydraulic hoses  | Self cleaning rear roller with integrated skids |
| Front hood with mechanical adjustment  | Attachment plate with self levelling device     |
| Adjustable skids   |   |

#### OPTIONS

|                                    |  |
|------------------------------------|--|
| Customized setting hydraulic motor | Possibility to have the rotor equipped with PML hammers or Y-flail |
| Stronger bearing for back roller   |  |

| MODEL                              | PMM/SSL-175 | PMM/SSL-200 |
|------------------------------------|-------------|-------------|
| <b>Engine</b> (hp)                 | 65-100      | 70-100      |
| <b>Flow rate</b> (L/min)           | 56-125      | 56-125      |
| <b>Pressure</b> (bar)              | 180-250     | 180-250     |
| <b>Working width</b> (mm)          | 1780        | 2020        |
| <b>Total width</b> (mm)            | 2000        | 2180        |
| <b>Weight</b> (kg)                 | 850         | 910         |
| <b>Rotor diameter</b> (mm)         | 440         | 440         |
| <b>Max shredding diameter</b> (mm) | 80          | 80          |
| <b>No. hammers</b> type PMM        | 22          | 24          |
| <b>No. flail</b> type Y/3          | 22          | 24          |

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

#### MAIN OPTIONS



Multiple flail



HAMMER PMM  
(standard)



FLAIL Y/3  
(option)