


THE ONLY PULL-BEHIND WORTHY OF BEING A GROUNDMASTER

The Groundsmaster® 1200 delivers an unparalleled combination of productivity, durability and superior cut. It features a 12 foot (3.7 meters) width of cut and can mow up to 8.73 acres (3.53 hectares) per hour. Remaining true to Groundsmaster's unmatched reputation of durability, the 1200 was designed for years of reliable mowing. Its spindles are the same as Toro's large rotaries and capable of withstanding the roughest conditions. The bi-directional impact resistant system provides additional protection to the wing decks. Don't let its productivity and robust design fool you; the Groundsmaster 1200's independently articulating decks hug undulations for an exceptional finish. Combine this with the dual roller design, the Groundsmaster 1200 delivers a high quality cut and rich turf striping in most conditions. Productivity, durability and exceptional cut. That's what makes the 1200 the only pull behind worthy of being a Groundsmaster.



FEATURES

• Maximum Productivity

The Groundsmaster® 1200 width of cut is 12 feet (3.7 m) and features a deck lift system allowing for the decks to be lifted from the turf while the PTO is engaged to quickly turn around without scuffing or transport over cart paths. This system helps keep the operator running at peak productivity.

• Simple Height of Cut Adjustment

The Groundsmaster® 1200 is not only a highly productive mower, it's also very versatile. Each deck features four mowing height adjustment points making it simple and quick to deliver the

exact mowing height for superior conditions. Height of cut up to 4" (10.2 cm).

• Quick Transport

The Groundsmaster® 1200 wing decks fold up near vertical for a narrow 86" (218.4 cm) transport width making it easy to get from site to site. Additionally, the transport wheels feature a torsion axle delivering a remarkably smooth ride making transport quick and comfortable. Compatible with Toro Outcross® 9060 and minimum 35 PTO horsepower (26 kW) tractors.

• Dual Rollers

The two full width rollers on the

front and rear of each deck help deliver an exceptional quality of cut. The front roller helps reduce scalping in undulated terrain while the rear roller delivers the exceptional turf striping. Each roller includes heavy-duty bearings featuring easy access grease points.

• Cutting Deck Protection

The Toro bi-directional impact absorption system was designed for an impact of 5 mph (8 km/h). The spring-loaded cylinder allows the deck to rotate upon impact. This rotating action absorbs the peak force experienced when an operator strikes an

object, protecting the main deck and frame components so you have less down time and more productivity.

• Robust Gearboxes

The deck gearboxes include an overrunning clutch that isolates the force from accidental blade impacts to keep the mower and tractor safe.

• Durable Spindles

Ductile cast iron spindle housing is large in diameter (9" or 229 mm at the base) to dissipate impact loads. Dual tapered roller bearings last up to six times longer than ball bearings.

GROUNDMASTER® 1200 SPECIFICATIONS

	GROUNDMASTER 1200 - MODEL 31905
WIDTH OF CUT	Overall: 12 feet (365 cm), Individual deck: 54" (137 cm), Overlap: 9" (23 cm)
MOWING RATE	Mows up to 8.73 acres/h (3.53 hectares/h) at 6 mph (9.7 km/h), assumes no overlap or stops
CONSTRUCTION	10-gauge high-strength steel constructed deck with 7-gauge bolt-in reinforcements. 7-gauge welded steel side skids with 5" (12.7 cm) diameter steel rollers.
DECK DRIVE	PTO drive-shaft drives 4-way gearbox, secondary drive-shafts drive individual deck gearboxes, spindles belt driven with spring tensioner pulley. Main drive-shaft fits standard 1-3/8" (3.5 cm), 6-spline tractor PTO and contains 80 deg CV joint. Deck gearbox contains over-running clutch.
HEIGHT OF CUT	0.5" to 4.0" (1.3 cm to 10.2 cm) infinitely variable
SPINDLES	1.25" (3.17 cm) diameter spindle shafts, 9" (22.9 cm) diameter conical ductile iron housing and two greasable tapered roller bearings. Driven counter-clockwise when viewed from the top.
BLADES	9 blades, 19" (48.3 cm) long, 2.5" (6.4 cm) wide, 0.25" (6.4 mm) thick
GROUND FOLLOWING	9 anti-scalp cups, one on each blade, two anti-scalp/stripping rollers on each deck. On each deck: two 5" (12.7 cm) diameter roller
WING PROTECTION	Bi-directional, impact absorption damper on each wing deck
OVERALL DIMENSIONS	Transport Height: 75.75" (192.4 cm) Transport Length: 145.5" (369.6 cm) (Hitch fully extended) Width: (decks down):149.8" (380.5 cm) Transport Width: 86" (218.4 cm) at 1/2" (1.27 cm) HOC
POWER REQUIREMENTS	Minimum 35 HP (26 kW) at the PTO, 540 RPM
BLADE TIP SPEED	15,000 ± 300 ft/min (4572 ± 91.4 m/min) at 540 PTO RPM
TYRES	20 X 10 - 10 6-ply K500 turf tread
WEIGHTS	Total weight = 2,984 lbs (1354 kg), Tongue Weight in Transport = 691 lbs (313 kg)
ACCESSORIES	Road light kit, Tow chain kit, Slow moving vehicle sign, Fender kit, Nylon blade cover kit
CUTTING UNIT ACCESSORIES	Roller scraper kit, MVP blade pack standard, MVP blade pack high lift, MVP blade pack atomic
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.
CERTIFICATION	Complies with American National Standards Institute (ANSI B71.4-2012)

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.
Refer to Operator's Manual for further information and instructions.

The Groundsmaster 1200 is manufactured
in Tomah, WI ISO 9002 Certified Plant.



toro.com.au

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

©2019 The Toro Company.
All Rights Reserved.
200-0012AU 09-2019



facebook.com/toroaus
twitter.com/toroaus
youtube.com/toroaustralia



Count on it.