

## FORESTRY MULCHERS FOR EXCAVATORS

# PMM/EX

### Mulcher with hammer/flail rotor for excavators.

The PMM/EX is a flail mower used to mulch underbrush, grass and bushes. It is equipped with a variable manual displacement hydraulic piston motor that can be set to the carrier's hydraulic specifications. The stronger roller supports (optional)

ensure the best performance and maximum reliability on difficult terrain. The flow control valve ensures minimal setup of the mulcher without adjustments or modifications to the hydraulic system of the excavator.

 55-145 L/min

 Ø 8 cm max

 6-13 t



**Steel counter-blades**  
helps mulch material into  
a smaller final size



**Self-cleaning support roller**

**Enclosed machine body**



**Stronger bearings  
for the support roller**



### STANDARD EQUIPMENT

|  |   |
|--|---|
| 32/65 cc variable manual displacement hydraulic piston motor | Bulkhead for hydraulic connections              |
| Flow control system valve                                    | Rear hood with mechanical adjustment            |
| Safety and anticavitation valve                              | Adjustable skids                                |
| Enclosed / anti dust machine body                            | Self levelling protection flaps                 |
| Motor enclosed in the frame                                  | Welded counterblades                            |
| Belt transmission  | Self cleaning rear roller with integrated skids |

### OPTIONS

|   |   |
|---|---|
| Customized setting hydraulic motor      | Attachment plate with self levelling device                         |
| Customized attachment bracket with pins | Possibility to have the rotor equipped with PML hammers or Y-flails |

| MODEL                              | PMM/EX-100 | PMM/EX-125 | PMM/EX-150 |
|------------------------------------|------------|------------|------------|
| <b>Flow rate</b> (L/min)           | 55-145     | 55-145     | 55-145     |
| <b>Pressure</b> (bar)              | 180-350    | 180-350    | 180-350    |
| <b>Excavator weight</b> (t)        | 6-13       | 6-13       | 6-13       |
| <b>Working width</b> (mm)          | 1060       | 1300       | 1540       |
| <b>Weight</b> (kg)                 | 520        | 600        | 680        |
| <b>Rotor diameter</b> (mm)         | 440        | 440        | 440        |
| <b>Max shredding diameter</b> (mm) | 80         | 80         | 80         |
| <b>No. hammers</b> type PMM        | 12         | 16         | 18         |
| <b>No. flails</b> type Y/3         | 12         | 16         | 18         |

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

### MAIN OPTIONS



**Customized setting  
hydraulic motor**



**Attachment plate with self  
levelling device**  
to adapt to all types of terrain



**Possibility to have the  
rotor equipped with PML  
hammers or Y-flail**



**HAMMER PMM**  
(standard)



**FLAIL Y/3**  
(option)