

## FORESTRY MULCHERS FOR EXCAVATORS

# UML/HY/RW - FML/HY/RW

### Forestry mulcher with fixed tooth rotor for excavators.

The UML/HY/RW mulcher has been specifically designed for railway vehicles or other special machines. It is ideal for maintaining areas that are difficult to reach such as the embankments of railway lines.

The optimum weight, light frame and oversized rotor equipped with fixed teeth, allows for the mulching of material up to 12 cm diameter. It will mulch even with the presence of stones or rocks found near railroads.

 65 - 180 L/min

 Ø 12 cm max

 6-10 t



**Steel counter-blades**  
helps mulch material into  
a smaller final size



**Hydraulic piston motor 63cc with relief  
and anticavitation valve**

**Motor enclosed in frame**  
protected from dirt and damage



**Swinging  
hammer rotor**  
(FML/HY/RW)



### MAIN OPTIONS



**Rotor with  
Bite Limiter technology**  
maximum productivity using  
the least amount of power



**Customized setting  
hydraulic motor**

### STANDARD EQUIPMENT

32/65cc variable manual displacement hydraulic piston motor (92-180 L/min) (UML/HY/RW - FML/HY/RW)	Belt transmission
55/38cc variable torque hydraulic piston motor (95-135 L/min) (UML/HY/RW/VT)	Bulkhead for hydraulic connections
Flow control system valve	Hydraulic rear hood
Safety and anticavitation valve	Screwed protection chains
Enclosed / anti dust machine body	Welded counterblades
Motor enclosed in the frame	

### OPTIONS

Customized setting hydraulic motor	Multiple tooth options
Rotor Bite Limiter	

MODEL	UML/HY/ RW-125	UML/HY/ RW-150	UML/HY/ RW/VT-125	UML/HY/ RW/VT-150	FML/HY/ RW-125	FML/HY/ RW-150
<b>Flow rate</b> (L/min)	92-180	92-180	90-135	90-135	65-165	65-165
<b>Pressure</b> (bar)	220-350	220-350	220-350	220-350	220-250	220-250
<b>Excavator weight</b> (t)	6-10	6-10	6-10	6-10	6-10	6-10
<b>Working width</b> (mm)	1342	1582	1342	1582	1342	1582
<b>Weight</b> (kg)	680	750	680	750	550	590
<b>Rotor diameter</b> (mm)	425	425	425	425	425	425
<b>Max shredding diameter</b> (mm)	120	120	120	120	120	120
<b>No. teeth</b> type C/3+C/3/SS	26+2	32+2	26+2	32+2	-	-
type I+C/3/SS	36+2	42+2	36+2	42+2	-	-
<b>No. hammers</b> type FML	-	-	-	-	20	24

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

### ROTOR TYPE C



**TOOTH C/3**  
(standard)



**TOOTH C/3/HD**  
(option)



**BLADE BL**  
(option)

### ROTOR TYPE BL



**BLADE BL**  
(option)

### ROTOR TYPE I



**TOOTH I**  
(option)



**TOOTH C/3/SS**  
(side scraper)



**HAMMER FML**  
(standard)